vPad Pro with HID Reader

Use two-factor authentication to release your SecurePrint print jobs

The vPad Pro with HID Reader is a touch screen and HID authentication device that is easy to install and integrate into your UniPrint Infinity printing environment. This device is compatible with all printer makes and models and therefore does not require printer fleet standardization. Simply use the printers you already have.

The perfect solution to enforce secure printing both in the head office and at all remote locations, the vPad Pro with HID Reader also supports print stream compression. By utilizing print stream compression, remote print servers can be consolidated to the data centre. The data centre print server compresses print data before transmission and the remote office vPad decompresses the print stream before sending it to a user-selected printer. The vPad Pro with HID Reader does not store any user or print job data, making this a truly secure printing solution.

Technical Specification:

CPU	Freescale i.MX357, ARM11 processor, 532 MHz
RAM	128MB SDRAM
ROM	512MB NAND Flash
Interfaces	Two Ethernet ports, 10/100 Mbps Two USB 2.0 One serial interface RS232
Screen Type & Size	7-inch resistive touch screen, TFT LCD (800 x 480)
Dimensions	9 x 6⅛ x 1¾ inches (228.6 x 155.6 x 44.5 mm)
Weight	1.7 lbs (755 g)
Color	Top: Metallic grey; Base: Black
Power Supply	Output: 5V; Input: 100 – 240V
Certifications	FCC (Part 15, Sub B), CE (EN55024 & EN55022 Class A/B), QPS Mark (Safety EN60950)
HID Reader	
Frequency	125 kHz
HID Cards Supported	ProxCard II, ISOProx II, DuoProx II, Smart ISO Prox II, Smart DuoProx II, iClass Prox , MIFARE /Prox, ProxCard Plus, ProxKey III, MicroProx Tag, ProxPass III
Certifications	FCC, CE, UL, RoHS